



UNIVERSITY
of SOPRON

11th Hardwood Conference

30-31 May 2024
Sopron

11TH HARDWOOD CONFERENCE PROCEEDINGS

Róbert Németh, Christian Hansmann, Holger Militz, Miklós Bak, Mátyás Báder



11TH HARDWOOD CONFERENCE PROCEEDINGS

Sopron, Hungary, 30-31 May 2024

**Editors: Róbert Németh, Christian Hansmann, Holger Miltz,
Miklós Bak, Mátyás Báder**



UNIVERSITY OF SOPRON PRESS

SOPRON, 2024

11TH HARDWOOD CONFERENCE PROCEEDINGS

Sopron, Hungary, 30-31 May 2024

Editorial board

Prof. Dr. Róbert Németh

Dr. Christian Hansmann

Prof. Dr. Holger Militz

Dr. Miklós Bak

Dr. Mátyás Báder

[University of Sopron](#) – Hungary

[FATE - Scientific Association for Wood Industry](#) – Hungary

[Wood K Plus](#) – Austria

[Georg-August University of Göttingen](#) – Germany

[University of Sopron](#) – Hungary

[University of Sopron](#) – Hungary

[FATE - Scientific Association for Wood Industry](#) – Hungary

Scientific committee

Prof. Dr. Dr. h.c. Peter Niemz

Prof. Dr. Dr. h.c. Alfred Teischinger

Prof. Dr. George I. Mantanis

Prof. Dr. Bartłomiej Mazela

Prof. Dr. Julia Mihailova

Prof. Dr. Joris Van Acker

Prof. Dr. Ali Temiz

Prof. Dr. Henrik Heräjärvi

Prof. Dr. Andreja Kutnar

Prof. Dr. Goran Milić

Dr. Vjekoslav Živković

Dr. Rastislav Lagana

Dr. Milan Gaff

Dr. Lê Xuân Phương

Dr. Peter Rademacher

Dr. Emilia-Adela Salca

Dr. Galina Gorbacheva

[ETH Zürich](#) – Switzerland / [Luleå University of Technology](#) – Sweden

[BOKU University Vienna](#) – Austria

[University of Thessaly](#) – Greece

[Poznań University of Life Sciences](#) – Poland

[University of Forestry](#) – Bulgaria

[Ghent University](#) – Belgium

[Karadeniz Technical University](#) – Turkey

[Natural Resources Institute Finland \(LUKE\)](#) – Finland

[InnoRenew CoE](#) – Slovenia

[University of Belgrade](#) – Serbia

[University of Zagreb](#) – Croatia

[TU Zvolen](#) – Slovak Republic

[Mendel University Brno](#) – Czech Republic

[Vietnam National University of Forestry](#) – Vietnam

[Eberswalde University for Sustainable Development](#) – Germany

[“Transilvania” University of Brasov](#) – Romania

[Bauman Moscow State Technical University](#) – Russian Federation

Cover design

Ágnes Vörös

[University of Sopron](#) – Hungary

Webservices

Dr. Miklós Bak

[11th Hardwood Conference official website](#)

[University of Sopron](#) – Hungary

ISBN 978-963-334-518-4 (pdf)

DOI <https://doi.org/10.35511/978-963-334-518-4>

ISSN 2631-004X (Hardwood Conference Proceedings)

Constant Serial Editors: Prof. Dr. Róbert Németh, Dr. Miklós Bak

Cover image based on the photograph of Dr. Miklós Bak, 2024

The manuscripts have been peer-reviewed by the editors and have not been subjected to linguistic revision.

In the articles, corresponding authors are marked with an asterisk (*) sign.

[University of Sopron Press](#), 2024 (Bajcsy-Zsilinszky 4, 9400 Sopron, Hungary)

Responsible for publication: Prof. Dr. Attila Fábián, rector of the [University of Sopron](#)

Creative Commons license: CC BY-NC-SA 4.0 DEED



Nevezd meg! - Ne add el! - Így add tovább! 4.0 Nemzetközi
Attribution-NonCommercial-ShareAlike 4.0 International

Sponsors: [University of Sopron](#), Hungary; [Wood K Plus](#), Austria; [Georg-August University of Göttingen](#), Germany; [Scientific Association for Wood Industry](#), Hungary



UNIVERSITY
of SOPRON

WOOD
KPLUS



FATE

Content

Preface to the 11TH HARDWOOD CONFERENCE

Róbert Németh..... 9

Plenary Session - Keynotes of the 11TH HARDWOOD CONFERENCE

- The role of black locust (*Robinia pseudoacacia*) in Czechia
Ivan Kuneš, Martin Baláš, Přemysl Šedivka, Vilém Podrázský 11
- Engineered wood products for construction based on beech and poplar resources in Europe
Joris Van Acker, Liselotte De Ligne, Tobi Hallez, Jan Van den Bulcke 23
- The situation in the hardwood sector in Europe
Maria Kiefer-Polz, Rainer Handl 60

Session I - Silvicultural aspects and forest management of hardwoods

- Monitoring xylogenesis as a tool to assess the impact of different management treatments on wood formation: A study case on *Vitis vinifera*
Angela Balzano, Maks Merela, Meta Pivk, Luka Krže, Veronica De Micco 62
- The History of Forests - Climate Periods of the Middle Ages and Forestry
Emese Berzsenyi, Dóra Hegyesi, Rita Kattein-Pornói, Dávid Kazai..... 63
- Climate change mitigation aspects of increasing industrial wood assortments of hardwood species in Hungary
Éva Király, Zoltán Börzsök, Attila Borovics..... 71
- Uncovering genetic structures of natural Turkey oak populations to help develop effective climate change strategies for forestry
Botond B. Lados, László Nagy, Attila Benke, Csilla É. Molnár, Zoltán A. Köbölkuti, Attila Borovics, Klára Cseke..... 78
- Ash dieback: infection biology and management
Nina E. Nagy, Volkmar Timmermann, Isabella Børja, Halvor Solheim, Ari M. Hietala..... 86
- The Role of Industrial Hardwood Production Plantations and Long-Term Carbon Sequestration in a Circular Economy via the New *Robinia pseudoacacia* ‘Turbo Obelisk’ Varieties
Márton Németh, Kálmán Pogrányi, Rezső Solymos..... 95
- Initial growth of native and introduced hardwoods at the afforested agricultural lands – preliminary results
Vilém Podrázský, Josef Gallo, Martin Baláš, Ivan Kuneš, Tama Abubakar Yahaya, Miroslav Šulitka
 102

Poster Session

- Light response curve analysis of juvenile Püspökladányi and Üllői black locust
Tamás Ábri, Zsolt Keserű, József Csajbók..... 111
- Revealing the optimum configuration of heat-treated wood dowel joints by means of Artificial Neural Networks and Response Surface Methodology
Bogdan Bedeleian, Cosmin Spîrchez..... 115
- Artificial neural networks as a predictive tool for thrust force and torque during drilling of wood-based composites
Bogdan Bedeleian, Mihai Ispas, Sergiu Răcășan 121

Research on the value retention of hardwood products in the spirit of sustainability <i>Daniel Bodorkós, József Zalavári, Péter György Horváth</i>	126
Abrasive Water Jet Cutting vs. Laser Jet Cutting of Oak Wood Panels <i>Camelia Cosereanu, Gheorghe Cosmin Spirchez, Antonela Lungu, Sergiu-Valeriu Georgescu, Alexandru Catalin Filip, Sergiu Racasan</i>	131
Polyphenol content of underutilized wood species from Hungary <i>Tamás Hofmann, Haruna Seidu, Kibet Tito Kipkoror</i>	136
Wood quality evaluation of 32 grafted clone linages of Keyaki (<i>Zelkova serrata</i>) plus trees 12 years after planting <i>Kiyohiko Ikeda, Shigehiro Yamamoto</i>	141
Influence of the number of belts over vibrations of the cutting mechanism in woodworking shaper <i>Georgi Kovatchev, Valentin Atanasov</i>	146
The impact of litter forest fires on the internal structure of wood from stem of beech trees <i>Elena-Camelia Musat, Costin-Ovidiu Vantoiu, Emilia-Adela Salca</i>	153
Analysing innovative wood joints crafted by laser cut spline curves <i>László Németh, József Garab, Péter György Horváth</i>	158
Dynamic fatigue tests of hardwoods <i>Gábor Orbán, Antal Kánnár</i>	163
Restoration of an old painted oak boardsign - A case study <i>Gabriel Calin Canalas, Emilia-Adela Salca, Elena-Camelia Musat</i>	168
Some physical properties of native and thermo-treated <i>Fraxinus excelsior</i> timber <i>Cosmin Spirchez, Aurel Lunguleasa, Alin Olărescu, Camelia Coşereanu, Bogdan Bedelea</i>	173
The surface morphology of sanded curly maple in comparison with straight grain maple selected for musical instruments <i>Mariana Domnica Stanciu, Lidia Gurau, Florin Dinulica, Catalin Constantin Roibu, Cristian Hiciu, Andrei Mursa, Marian Stirbu</i>	178
Analysis of changes in the composition of beech as an important industrial raw material in Hungary <i>Katalin Szakálosné Mátyás, Attila László Horváth</i>	183
Investigation of old hardwood structure element <i>Fanni Szőke, Antal Kánnár</i>	187
An investigation of the influence of coating film thickness on the light induced colour changes of clear coated maple (<i>Acer pseudoplatanus</i>) wood surfaces with natural aspect <i>Mihai-Junior Torcătoru, Maria Cristina Timar</i>	192
Composite Material Manufacturing from Plantation Paulownia Wood with Using Microwave Technology: Technical and Cost Analyses <i>Grigory Torgovnikov, Peter Vinden, Alexandra Leshchinskaia</i>	198
Thermal modification of wood as a tool for changing the colour of hardwoods <i>Vidholdová Zuzana</i>	203
High termite resistance of kempas (<i>Koompassia malaccensis</i>) hardwood protected with a novel vegetal extracts-cypermethrin wood preservative under outdoor aboveground tropical environment <i>Messaoudi Daouia, Wong Andrew H.H.</i>	209
Comparison of wood properties of pedunculate oak and non-native northern red oak from an anthropogenic site <i>Aleš Zeidler, Vlastimil Borůvka</i>	214
Acoustic Parameters of Pioneer Wood Species <i>Petr Horák, Vlastimil Borůvka</i>	219
Determination of Elastic Parameters of Birch and Oak Wood Using Optical Method <i>David Novák, Vlastimil Borůvka, Petr Horák, Tomáš Kytka</i>	224

Preliminary study on climate change impacts on annual wood growth development in Hungary <i>Péter Farkas, Zsolt György Tóth, Huba Komán</i>	230
Combustion characteristics of Russian olive (<i>Elaeagnus angustifolia</i> L.) <i>Szabolcs Komán, Krisztián Töröcsi</i>	236
Withdrawal capacity of Green ash (<i>Fraxinus pennsylvanica</i> Marsh.) and Box elder (<i>Acer negundo</i> L.) <i>Szabolcs Komán, Boldizsár Déri</i>	241
Formaldehyde emission from wood and wood-based products <i>Szabolcs Komán, Csilla Czók, Tamás Hofmann</i>	246
Finite element analysis of heat transfer of Turkey oak (<i>Quercus cerris</i>) <i>Sándor Borza, Gergely Csiszár, József Garab, Szabolcs Komán</i>	250
Possible alternative to creosote treated railway sleepers, Fürstenberg-System Sleeper (FSS) <i>Szabolcs Komán, Balogh Mátyás Zalán, Sándor Fehér</i> ,.....	255
Investigation of bendability characteristics of wood-based polymer composites <i>S. Behnam Hosseini, Milan Gaff</i>	260
Comparing the blossoming and wood producing properties of selected black locust clones <i>Alexandra Porcsin, Katalin Szakálosné Mátyás, Zsolt Keserű</i>	266
The influence of two different adhesives on structural reinforcement of oak-wood elements by carbon and glass fibres <i>Andrija Novosel, Vjekoslav Živković</i>	271
Investigating Kerf Topology and Morphology Variation in Native Species After CO ₂ Laser Cutting <i>Lukáš Štefančín, Rastislav Igaz, Ivan Kubovský, Richard Kminiak</i>	272
Comparison of fluted-growth and cylindrical hornbeam logs from Hungarian forests <i>Mátyás Báder, Maximilián Cziczzer</i>	279
Thermal modification affects the dynamic vapor sorption of tree of heaven wood (<i>Ailanthus altissima</i> , Mill.) <i>Fanni Fodor, Lukas Emmerich, Norbert Horváth, Róbert Németh</i>	285
How conditions after application affect the depth of penetration of gel wood preservative in oak <i>Jan Baar, Štěpán Bartoš, Anna Oberle, Zuzana Paschová</i>	290
The weathering of the beech wood impregnated by pigmented linseed oil <i>Jakub Dömény, Jan Baar</i>	294
Examination of the durability of beeswax-impregnated wood <i>Miklós Bak, Ádám Bedők, Róbert Németh</i>	299
Preparation of pleated oak samples and their bending tests at different moisture contents <i>Pál Péter Gecseg, Mátyás Báder</i>	304
Bending test results of small-sized glued laminated oak timber consisting of 2, 3 and 5 layers <i>Dénes Horváth, Sándor Fehér</i>	308
Homogenized dynamic Modulus of Elasticity of structural strip-like laminations made from low-grade sawn hardwood <i>Simon Lux, Johannes Konnerth, Andreas Neumüller</i>	314
Impact of varnishing on the acoustic properties of sycamore maple (<i>Acer pseudoplatanus</i>) panels <i>Aleš Straže, Jure Žigon, Matjaž Pavlič</i>	319
The effect of wood and solution temperatures on the preservative uptake of Pannonia poplar and common spruce – preliminary research <i>Luca Buga-Kovács, Norbert Horváth</i>	325

Session II - Hardwood resources, product approaches, and timber trade

Birch tar – historic material, innovative approach <i>Jakub Brózdowski, Monika Bartkowiak, Grzegorz Cofa, Grażyna Dąbrowska, Ahmet Erdem Yazici, Zbigniew Katolik, Szymon Rosołowski, Magdalena Zborowska</i>	330
Beech Wood Steaming – Chemical Profile of Condensate for Sustainable Applications <i>Goran Milić, Nebojša Todorović, Dejan Orčić, Nemanja Živanović, Nataša Simin</i>	336
Towards a complete technological profile of hardwood branches for structural use: Case study on Poisson's ratio <i>Tobias Nennung, Michael Grabner, Christian Hansmann, Wolfgang Gindl-Altmutter, Johannes Konnerth, Maximilian Pramreiter</i>	342
Low-value wood from non-native tree species as a potential source of bioactive extractives for bio-based preservation <i>Viljem Vek, Ida Poljanšek, Urša Osolnik, Angela Balzano, Miha Humar, Primož Oven</i>	349
Hardwood Processing - do we apply appropriate technologies? <i>Alfred Teischinger</i>	357

Session III - Surface coating and bonding characteristics of hardwoods

Influence of pretreatments with essential oils on the colour and light resistance of maple (<i>Acer pseudoplatanus</i>) wood surfaces coated with shellac and beeswax <i>Emanuela Carmen Beldean, Maria Cristina Timar, Dana Mihaela Pop</i>	365
Oak timber cross-cutting based on fiber orientation scanning and mechanical modelling to ensure finger-joints strength <i>Soh Mbou Delin, Besseau Benoit, Pot Guillaume, Viguiet Joffrey, Marcon Bertrand, Milhe Louis, Lanvin Jean-Denis, Reuling Didier</i>	376
From Phenol-Lignin Blends towards birch plywood board production <i>Wilfried Sailer-Kronlachner, Peter Bliem, Hendrikus van Herwijnen</i>	386
Flatwise bending strength and stiffness of finger jointed beech lamellas (<i>Fagus sylvatica</i> , L.) using different adhesive systems and effect of finger joint gap size <i>Hannes Stolze, Adefemi Adebisi Alade, Holger Militz</i>	395
Mode I fracture behaviour of bonded beech wood analysed with acoustic emission <i>Martin Capuder, Aleš Straže, Boris Azinović, Ana Brunčič</i>	402

Session IV - Hardwood structure and properties

Compression strength perpendicular to grain in hardwoods depending on test method <i>Marlene Cramer</i>	410
Compensatory Anatomical Studies on <i>Robinia</i> , <i>Sclerocarya</i> and <i>Ulmus</i> <i>Fath Alrhman A. A. Younis, Róbert Németh, Mátyás Báder</i>	420
The influence of the type of varnish on the viscous-elastic properties of maple wood used for musical instruments <i>Roxana Gall, Adriana Savin, Mariana Domnica Stanciu, Mihaela Campean, Vasile Ghiorghe Gliga</i>	426
XRF investigation of subfossil oak (<i>Quercus</i> spp) wood revealing colour - iron content correlation <i>Nedelcu Ruxandra, Timar Maria Cristina, Beldean Emanuela Carmen</i>	435
Investigating the Development of Heartwood in <i>Quercus robur</i> in Denmark <i>Andrea Ponzeccchi, Albin Lobo, Jill Katarina Olofsson, Jon Kehlet Hansen, Erik Dahl Kjær, Lisbeth Garbrecht Thygesen</i>	445

Modelling tensile mechanical properties of oak timber from fibre orientation scanning for strength grading purpose <i>Guillaume Pot, Joffrey Viguier, Benoit Besseau, Jean-Denis Lanvin, Didier Reuling</i>	452
Green oak building – small diameter logs for construction <i>Martin Huber, Franka Brüchert, Nicolas Hofmann, Kay-Uwe Schober, Beate Hörnel-Metzger, Maximilian Müller, Udo H. Sauter</i>	461
An evaluative examination of oak wood defect detection employing deep learning (DL) software systems. <i>Branimir Jambreković, Filip Veselčić, Iva Ištok, Tomislav Sinković, Vjekoslav Živković, Tomislav Sedlar</i>	466
Comparison of surface roughness of milled surface of false heartwood, mature wood, and sapwood within beech wood <i>Lukáš Adamčík, Richard Kminiak, Adrián Banski</i>	467

Session V - Hardwoods in composites and engineered materials

Developing Laminated Strand Lumber (LSL) based on underutilized Hungarian wood species <i>László Bejő, Tibor Alpár, Ahmed Altaher Omer Ahmed</i>	475
Feasibility study on manufacturing finger-jointed structural timber using <i>Eucalyptus grandis</i> wood <i>Adefemi Adebisi Alade, Hannes Stolze, Coenraad Brand Wessels, Holger Militz</i>	481
A novel approach for the design of flame-retardant plywood <i>Christian Hansmann, Georg Baumgartner, Christoph Preimesberger</i>	486
The use of beech particles in the production of particleboards based on recycled wood <i>Ján Iždinský, Emilia Adela Salca, Pavlo Bekhta</i>	493
Thermal properties of highly porous wood-based insulation material <i>Kryštof Kubista, Přemysl Šedivka</i>	501

Session VI - Modification & functionalization

Quantitative and qualitative aspects of industrial drying of Turkey oak lumber <i>Iulia Deaconu, Bogdan Bedeleian, Sergiu Georgescu, Octavia Zeleniuc, Mihaela Campean</i>	508
Changes in properties of maple by hygrothermally treatment for accelerated ageing at 135-142°C <i>Tobias Dietrich, Herwig Hackenberg, Mario Zauer, Holger Schiema, André Wagenführ</i>	518
Change of chemical composition and FTIR spectra of Turkey oak and Pannonia poplar wood after acetylation <i>Fanni Fodor, Tamás Hofmann</i>	525
Change of cellulose crystal structure in beech wood (<i>Fagus sylvatica</i> L.) due to gaseous ammonia treatment <i>Herwig Hackenberg, Tobias Dietrich, Mario Zauer, Martina Bremer, Steffen Fischer, André Wagenführ</i>	535
Evaluation of weathering performance of acetylated hardwood species <i>Rene Herrera Diaz, Jakub Sandak, Oihana Gordobil, Faksawat Poohphajai, Anna Sandak</i>	539
Unlocking a Potential Deacetylation of Acetylated Beech (<i>Fagus sylvatica</i> L.) LVL <i>Maik Slabohm, Holger Militz</i>	544
Fork and flying wood tests to improve prediction of board stress development during drying <i>Antoine Stéphane, Patrick Perré, Clément L'Hostis, Romain Rémond</i>	549
Modification of different European hardwood species with a bio-based thermosetting resin on a semi-industrial scale <i>Christoph Hötte, Holger Militz</i>	557

Investigation of old hardwood structure element

Fanni Szőke^{1*}, Antal Kánnár¹

¹ University of Sopron, Creative Industry Institute, Bajcsy-Zs. Str. 4., Sopron, Hungary, 9400

Email: fanni.szoke1@gmail.com; kannar.antal@uni-sopron.hu

Keywords: Lookout tower; Solid wood; Electron microscopy; Dynamic Modulus of Elasticity; compression strength; bending strength

ABSTRACT

This paper reports on the structural testing of the dismantled Kecske hill lookout tower. The wooden structure stood in the Szárhalom forest, near Sopron, Hungary. It was erected in 1973, closed off in 2018 due to the failure of its structural elements, and finally demolished in 2021. Structural elements were tested and evaluated after 45 to 48 years of service, using, among others, electron microscopy, dynamic modulus of elasticity measurements, compression and bending tests. A literature review was conducted on the structural details of lookout towers, on the characteristics and production technology of glued-laminated wood, as well as the examined materials, including Norway spruce (*Picea abies*) and sessile oak (*Quercus petraea*). Literature values of compression and bending strength were also determined to compare them to our results. The analysis extended to describing the details of the new lookout tower, including the footing and stair installations, which were the main failure locations in the old structure. Based on the results, samples cut from the undamaged parts of the old structure had high residual strength even after 45 years of service, but the structure as a whole was no longer safe, due to the failure of certain elements.

INTRODUCTION

The old structure under investigation was made of Norway spruce (*Picea abies*) and Sessile oak (*Quercus petraea*), while the new, current edifice has a larger variety of materials. Columns are made of GL24h glulam and beams are C24 softwood. A mixture of larch and oak were used for the stairs and decking.

The structural utility of one of the examined species, Norway spruce (*Picea abies*) largely depends on knots. It is prone to warping, but its strength and elastic properties are excellent. Based on literature data, its compression strength and bending strength ranges between 35-50-79 MPa and 49-78-136 MPa (at 12% MC, Molnár 2016).

The compression strength and bending strength of Sessile oak (*Quercus petraea*) at 12% MC is 55.7 MPa and 112.4 MPa, respectively, while its density is 750 kg/m³ (Molnár – Farkas 2016).

During an inspection in the summer of 2018, the owner TAEG Forest Enterprise realised that the ends of the structural beams and other elements have deteriorated, rendering the lookout tower unsafe to use. The tower was cordoned off, and the lower steps removed to restrict access. The old lookout tower was finally dismantled in September 24, 2021. Specimens were accrued from the owner after landfilling the debris in October. Samples were collected from various places within the structure, described in detail in the testing section.

Selected samples were transported to the Timber Structures Testing Laboratory of the Institute of Applied Mechanics and Structures of the Sopron University for testing. To protect the cutting and testing machines, nails, bolts and other pieces of hardware were removed from the material. Testing took place after this, starting with non-destructive measurements and then strength testing.

Several measurements were made on the structure. Methods, results and conclusions are discussed separately for the various tests. Second level headings will introduce these tests for electron microscopy, non-destructive testing, compression and bending, respectively.

EXPERIMENTAL METHODS

Dynamic Modulus of Elasticity Measurements

Dynamic Modulus of Elasticity (MOE) testing was done using the non-destructive PLG testing equipment, developed in Hungary, based on sound velocity measurement. This instrument measures the density, MOE and estimates the bending strength. The instrument determines the stress grade according to MSZ EN 338 for softwoods. In case of oak, we determined the grade ourselves, based on the standard.

Compression tests

Compression strength is the resistance capacity of wood against loading along or across the fibres. Investigations included both cylindrical and rectangular specimens of materials that had been loaded in compression in the original structure as well. Measurements included 5 cylindrical and 2 rectangular oak, as well as 2 sound but checked spruce specimens. Specimens were placed in a Matest Servo-Plus Evolution (3000 kN capacity) material testing machine that subjected them to a gradually increasing pressure at a rate of 0.6 MPa/s. The determination of the strength values followed values in the table “Eurocode5 stress grades of wood”. Since literature values pertain to air-dry moisture content, these values were converted to 12% MC, as indicated in the tables.

Bending tests

Four-point bending tests were used to compare the bending strength of oak with literature values. The advantage of the four-point bending scheme, compared to 3-point bending is that failure occurs in clear bending. Shear failure may occur due to the shortness of the specimen. The machine loaded the specimen at a rate of 0.500 kN/s, and stopped the test after failure when the load fell back to 50% of the ultimate level. The moisture content at the time of testing was 15%, and the values were converted to 12% before assigning the stress grades.

RESULTS

Dynamic Modulus of Elasticity Measurements

8 specimens were measured as described above. The results of the dynamic MOE measurements show the mean of the spruce 11668 MPa, the oak specimen MOE 11270 MPa. The samples were also classified into the appropriate stress grade based on the results, which showed C22, C27 and D18, D30, D35, D50 categories, but in case of the Nr. 3 specimen it was out of grade. The Moisture Content of the material was 18%. The instrument converted the measured data to 12% MC as the standard MC value. (Table 1, Figure 1)

Table 1: The results of the dynamic MOE measurements

Nr.	Species	l [m]	w [mm]	h [mm]	m [kg]	ρ [kg/m³]	MOE [MPa]	Stress grade
1	Spruce	1.36	160	160	13.62	379	11009	C22
2	Spruce	1.47	140	140	12.52	420	12326	C27
3	Oak	1.11	135	55	5.46	652	8571	out of grade
4	Oak	1.52	140	140	21.60	705	11393	D30
5	Oak	1.13	260	50	11.24	742	11762	D30
6	Oak	1.16	220	45	8.30	702	14011	D50
7	Oak	1.17	250	50	9.34	619	9682	D18
8	Oak	1.16	245	45	10.80	822	12205	D35

The Moisture Content of the material was 18%. The instrument converted the measured data to 12% MC as the standard MC value, and the values in Table 1 are these converted values.




Figure 1: The measured Dynamic MOE values

Compression tests

Results of the air dry (12%) values show that the compression strength of spruce (mean: 57,5 MPa) reach and even exceed those of oak (mean: 45,8 MPa). One explanation may be that fluctuating climatic conditions induced higher stresses in oak, and thus created a larger number of drying fissures throughout the years. These fissures acted as fracture initiation locations during the failure process and manifested as a kind of cross sectional area reduction. (Figure 2)




Figure 2: A comparison of compression strength values at air dried MC (u=12%)

Bending tests

The specimens show the mean of bending strength (u = 12%) 64.25 MPa. The samples were also classified into the appropriate stress grade based on the results, which showed D50, D60, D70 categories. All of them belong to one of the three highest stress grades. Specimens cut from the sound sections of the elements had high bending strength. (Table 2)

Table 2: The results of the bending tests

	a [mm]	b [mm]	u [%]	F [kN]	σ [MPa] (u=15%)	σ [MPa] (u=12%)	τ [MPa]	Stress grade
spec. nr. 1	45	90	15	21.023	51.908	58.137	7.786	D50
spec. nr. 2	45	90	15	21.210	52.370	58.654	7.856	D50
spec. nr. 3	45	90	15	29.170	75.025	84.028	10.804	D70
spec. nr. 4	45	90	15	22.074	54.504	61.045	8.176	D60
spec. nr. 5	45	90	15	19.500	48.148	53.926	7.222	D50
spec. nr. 6	45	90	15	25.202	62.227	69.694	9.334	D60
Mean	-	-	-	23.030	57.364	64.247	8.530	-
Minimum	-	-	-	19.500	48.148	53.926	7.222	-
Maximum	-	-	-	29.170	75.025	84.028	10.804	-
Std.	-	-	-	3.553	9.832	11.012	1.316	-
Var%	-	-	-	15.430	17.141	17.141	15.431	-

Table 2 shows the measurement data, where a is width, b is height, u is moisture content, F is the ultimate load in kN, which is half of the maximum force measured, due to the two-point loading, σ is bending strength, τ is the shear stress generated during bending.

DISCUSSION

Dynamic Modulus of Elasticity Measurements

MOE values are nearly identical for all specimens. Spruce and oak specimens yielded densities typical of these species. The MOE values of spruce calculated based on stress-wave velocity indicate medium quality. The measured MOE values of around 11,000 N/mm² correspond to medium stress grades in coniferous beams. Failure primarily occurred near the bolted connections; in farther positions, wood integrity was unaffected. The density and MOE of oak planks, in contrast, show significant variation. One of the specimens did not even reach an MOE value necessary to be classified as the lowest grade of D18. Four of the six specimens received low grades, i.e. the oak specimens showed a lowered strength after four decades.

Compression tests

Cylindrical specimens clearly show almost identical values and diagram shapes, due to the similar characteristics arising from the same species. In the diagrams of the rectangular samples, on the other hand, the differences between the two species in terms of Modulus of Elasticity, proportional to the slope of the linear portion, are clearly visible. Compared to spruce, oak specimens exhibit much steeper curves, due to the higher MOE of oak. Oak's more intensive initial checking may have caused the lower strength of these specimens. When compared to the characteristic values of 34 N/mm² set forth in the table for the stress grade D70 for hardwoods, these specimens exceed this value significantly, by approx. 34%. The compression strength of the columns was generally high. The failure, again, occurred at the connections, as demonstrated before.

Bending tests

Compared to values in each hardwood stress grade, the bending strength of the oak specimens proved to be outstanding. All of them belong to one of the three highest stress grades. Specimens cut from the sound sections of the elements had high bending strength. The failure of the structure was caused by fungal deterioration due to wetting, primarily in the proximity of the connections.

The new lookout tower

While inspecting the new lookout tower, which was built in 2022, we detected delamination at one of the glulam elements at the anchoring site. Vanya, Kannar and Rabb (2016) showed that „ bolted connections, which hinder shrinkage and swelling through concentrated loads at the bolts, may result in the creation of cracks”, but „nailplate type connectors hold the load bearing element together, and small stress peaks generated at many locations hinder the deformation, thus no significant cracking occurs. Thus, improving nailplate type connections is recommended” (Vanya – Kánnár – Rabb 2016). In another analysis, Kánnár (2011) and Vanya (2014) identified possible reasons as follows: „Delamination in glued-laminated structures may have occurred due to multiple factors, such as: restricted shrinkage and

swelling, lamella runout, moisture differences among lamellas, stresses perpendicular to the axis of the beam, adhesion problems, wood's anisotropic and inhomogeneous material properties, and the visual, rather than instrumented stress grading of the lamellas" (Kánnár 2011) (Vanya 2014). The cause of failure was stresses perpendicular to the axis of the beam, caused by the bolted connection. This may lead to wood protection problems later, since a subsequent growth of the crack may lead to wetting, and later rotting. Sealing the crack using waterproof caulking may prevent this eventuality. This is especially important in case the crack becomes wider, since wind load and occupancy load continuously change the loads in the new structure. At present, continuous monitoring of the crack during periodic inspections is sufficient. The other parts of the lookout tower are in good condition, and well-executed work.

CONCLUSIONS

There are many factors to consider in structural design. The structure should provide the intended utility value with respect to the service life and financial aspects. It should reliably resist loads arising from external loads and climate-induced stresses, which may arise during erection or use. In case of accidental actions like earthquakes fire of human errors, damage should be proportional.

During our investigation, we analysed the elements of the dismantled structure to establish the causes of failure. Based on the results, specimens cut out of the sound portion of the elements had high residual strength, and the failure of the structure was caused by the rotting of the columns, primarily in the proximity of the connections, which could thus no longer safely support the otherwise still serviceable elements. It is important to limit the extent of the damages already in the design phase, but also keep it to a minimum during construction and maintenance as well, so that the edifice can fulfil its structural purpose during the intended lifespan.

REFERENCES

- Bodig J., Jayne B. A. (1982): *Mechanics of Wood and Wood Composites*. Van Nostrand Reinhold, 1982. Michigan, Michigan State University. pp. 291.
- Kánnár A. (2011): Theoretical and experimental investigations of damage development of glulam beams The 17th International Nondestructive Testing and Evaluation of Wood Symposium 2011. szept. 14-16. Sopron Hungary. Proceedings 367-374.
- Kánnár A. (2014): A faanyag mikro- és makro-tönkremeneteli folyamatai, [Microscopic and macroscopic failure processes in wood.] Sopron, ISBN 978-963-08-8672-7, pp. 6-7., pp. 12. (in Hungarian)
- Molnár S., Farkas P. (2016): Tölgy (kocsányos és kocsánytalan tölgy) – *Quercus spp.*, In: *Földünk ipari fái*, Eds. Molnár S., Farkas P., Börcsök Z., Zoltán Gy., Photog. Richter, H.G. & Szeles P., ERFARET Nonprofit Kft., Sopron, ISBN 978-963-12-5239, pp. 121-126. (in Hungarian)
- Molnár S. (2016): Lucfenyő – Norway Spruce, In: *Földünk ipari fái*, Eds. Molnár S., Farkas P., Börcsök Z., Zoltán Gy., Photog. Richter, H.G. & Szeles P., ERFARET Nonprofit Kft., Sopron, ISBN 978-963-12-5239, pp. 89-91. (in Hungarian)
- Vanya Cs., Kánnár A., Rabb, P. (2016): Javaslatok rétegelt-ragasztott fatartók tervezéséhez, gyártásához és üzemeltetéséhez, felmérési és modellezési eredmények alapján – III. rész: A tönkremeneteleket igazoló vizsgálatok és eredményei. [Design, fabrication and operation proposals for glued laminated timber, based on measuring and modelling results. Chapter 3: Failure examinations and their results.] *Faipar*, 62. évf. 1. sz. (2016), <https://doi.org/10.14602/WOODSCI.2016.1.45> (in Hungarian)